

Pollboom™ Permanent Booms

PollBoom™ Permanent oil containment booms, also known as permanent spill control booms, are the most durable booms, with superior uv resistance, tear resistance, and tensile strength.

These heavy-duty booms are engineered for installations which are permanent or long term in nature.

These booms are manufactured with PVC/ PU Coated fabric and foam filled shells that make the boom function even in rough conditions.

Features :

- PVC Coated Belting Fabric

- Polyethylene Foam Shells
- Connectors: ASTM Z design as per ASTM F962
- Boom designs comply as per ASTM F1523



PollBoom Permanent Boom Specifications

TECHNICAL DATA	PB500PFB	PB600PFB	PB750PFB	PB900PFB
HEIGHT (mm)	500	600	750	900
FREEBOARD (mm)	200	250	300	350
DRAUGHT (mm)	300	350	450	550
SECTION LENGTH(m)	25, 50			
WEIGHT (Kg/Meter) (ASTM-F818-16)	2.3	3.4	4	4.3
BOOM TENSILE STRENGTH (kg) (ASTM-F1093-99)	3700	3700	3700	3700
FLOATS	Foam Filled chambers with HDPE floats			
FABRIC	PVC / PU available			
CONNECTORS	Stainless steel U-bolt/ Aluminium ASTM Z-type			

ENVIROGUARD SOLUTIONS LLP

D / 2A Ghatkopar Industrial Estate, LBS Marg, Ghatkopar West, Mumbai 400086.

T: +91 22 49716204 | E: sales@enviroguardsolutions.com

LLP Number: AAH - 9886. Registered in India.

www.enviroguardsolutions.com