



By **EnviroGuard Solutions**

Pollisorb Oil Absorbent Rolls

PSMWSRMBO,

Plain, Medium Weight

Dimensions : 38 cm x 46 m

Basis : 286 Gsm

Absorbency : 70 Litres

Quantity/Unit : 1



FEATURES

- Economical Choice to absorb Oil based fluids
- High absorbency with plain construction
- Does NOT absorb water
- Floats on water
- Fire Retardant as per ASTM 726
- Rolls are ideal for cleaning up spills over a larger surface area
- Medium weight construction suitable for general day to day clean-ups and operations

APPLICATIONS

- Lubricants
- Hydraulic Oils
- Cooking Oils
- Vegetable Oils
- Transformer Oils
- Other oil based liquids

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and clean-up materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur"