

Pollboom™ Shore Sealing Boom

The PollBoom™ range of Shore Sealing Booms are manufactured with a robust design to cater to the sealing of shores from Oil Spills.

The PollBoom™ range of Shore Sealing booms are manufactured in PVC / PU Fabric in high visibility Orange color. These booms consist of two level of chambers, the upper being air filled and the lower ones being water filled. Each air chamber is equipped with 1 no of Monsun valve and the water filled chambers with 2 nos of valves.

Beach sealing booms are provided with ASTM

Connectors as a standard connection to the offshore boom that is used by the relevant authority.

The booms come in two different heights, 40cm and 56cm.

Features :

- High visibility orange color
- Easily connectable to existing boom
- Designed for Land water interface
- Material: PVC / PU Fabric
- Connectors: ASTM Z design as per ASTM F962
- Boom designs comply as per ASTM F1523



PollBoom Shore Sealing Boom Specifications

TECHNICAL DATA	PB400SSB	PB560SSB
HEIGHT (mm)	400	560
FREEBOARD (mm)	150	230
DRAUGHT (mm)	250	330
SECTION LENGTH(m)	10	
WEIGHT (Kg/Meter) (ASTM-F818-16)	2.3	3.4
BOOM TENSILE STRENGTH (kg) (ASTM-F1093-99)	3700	3700
FLOATS	Air and Water Filled Chambers	
FABRIC	PVC / PU available	
CONNECTORS	Stainless steel U-bolt/ Aluminium ASTM Z-type	

ENVIROGUARD SOLUTIONS LLP

D / 2A Ghatkopar Industrial Estate, LBS Marg, Ghatkopar West, Mumbai 400086.

T: +91 22 49716204 | E: sales@enviroguardsolutions.com

LLP Number: AAH - 9886. Registered in India.

www.enviroguardsolutions.com